

- 400°C-2 saat yangın dumanını egzoz edebilme
- Motor hava akımı dışında
- Korozyona dayanımlı alüminyum şapka
- Yüksek verimli geriye eğik seyrek kanatlı galvaniz çelik sac kanatlar
- Galvaniz çelik sac tel kafes ve montaj plakası
- F sınıfı izolasyonlu, IP 55 asenkron elektrik motorları
- Frekans değiştirici ile %25 - %100 aralığında hız kontrolü
- Endüstriyel mutfak davlumbaz uygulamalarında kullanıma uygun
- Opsiyonel KITV aksesuar paketi ile dikey atışlı kullanım imkanı

- Smoke exhaust with the motor outside of hazardous area (400°C - 2 hours certified)
- The motor is outside of airstream
- High corrosion resistant aluminum roof cowl
- High efficient backward curved impeller is made up of galvanized steel sheet
- Bird protection guard and roof base support are made up of galvanized steel sheet
- Standard asynchronous motors with IP 55 and F class insulation
- Frequency inverters are optional to control the capacity in the range of %25 - %100.
- Suitable for industrial and professional kitchen hoods
- The KITV accessory is optional for vertical discharge exhaust



VENCO MODEL	CTH3-A 355 T4	CTH3-A 400 T4	CTH3-A 450 T4	CTH3-A 500 T4	CTH3-A 560 T4	CTH3-A 630 T6	CTH3-A 710 T6	CTH3-A 800 T6	CTH3-A 900 T6	CTH3-A 1000 T8
Voltaj / Voltage (V)	400	400	400	400	400	400	400	400	400	400
Güç / Power (kW)	0,55	0,75	1,1	1,5	3	1,5	2,2	4	11	7,5
Akım / Current (A)	1,49	1,63	2,49	3,26	6,17	3,71	5,94	9,46	22,6	17
Devir / Rev. (rpm)	1440	1410	1450	1450	1420	940	965	960	965	725
Ağırlık / Weight (kg)	19	21	38	50	55	70	170	205	250	411
□A	664,6	664,4	774,6	939,6	939,6	939,6	1134,6	1134,6	1411,19	1411,19
B _{aprox.}	645	702,75	758,15	863,65	880,65	922,65	1116,22	1142,72	1366,15	1436,55
□C	665	665	665	939	939	939	1035	1035	1365	1365
D	520	520	520	710	710	710	840	840	1210	1210
ØE	9	9	9	9	9	9	9	9	20	20
□F	253	253	253	353	353	353	453	453	453	453
G	210,8	268,75	304,25	319,5	336,5	378,5	441,5	468	541	611,5
H	40	40	40	50	50	50	50	50	50	50
I	30,75	30,75	30,75	31	31	31	31	31	41,5	41,5
K _{aprox.}	363,25	363,25	383,15	463,15	463,15	463,15	593,72	593,72	733,65	733,65

CTH3-A ÇATI TİPİ SANTRİFÜJ DUMAN EGZOZ FANLARI

CTH3-A ROOF TYPE CENTRIFUGAL SMOKE EXHAUST FANS

Statik (Pa) Static (Pa)	HAVA DEBİSİ (m ³ /h) / AIR FLOW								
	CTH3-A 355 T4	CTH3-A 400 T4	CTH3-A 450 T4	CTH3-A 500 T4	CTH3-A 560 T4	CTH3-A 710 T6	CTH3-A 800 T6	CTH3-A 900 T6	CTH3-A 1000 T8
0	3580	5400	7600	10200	13200	19000	25000	37740	39597
25	3482	5220	7427	9880	12822	18688	24617	37320	38982
50	3385	5105	7310	9757	12688	18414	24305	36905	38375
75	3282	4992	7191	9628	12549	18123	23995	36490	37772
100	3172	4870	7071	9498	12407	17828	23668	36075	37170
125	3054	4739	6941	9362	12265	17523	23342	35660	36565
150	2925	4603	6807	9218	12118	17195	22996	35246	35955
175	2788	4460	6670	9071	11961	16860	22648	34830	35337
200	2639	4314	6530	8920	11807	16517	22271	34408	34710
225	2465	4150	6377	8764	11643	16148	21887	33982	34068
250	2270	3967	6215	8601	11480	15747	21504	33552	33410
275	2035	3780	6046	8425	11307	15328	21083	33115	32732
300	1728	3576	5866	8247	11136	14900	20654	32671	32029
325		3332	5680	8052	10953	14423	20194	32218	31295
350		3057	5469	7851	10759	13893	19730	31755	30525
375		2711	5249	7636	10566	13323	19224	31280	29710
400		2261	5002	7406	10358	12700	18691	30793	28838
425			4721	7157	10139	11984	18112	30290	27894
450			4402	6886	9915	11128	17492	29770	26856
475			4033	6590	9679	10120	16850	29231	25688
500			3534	6266	9438	8712	16123	28668	24332
525				5881	9172	6541	15306	28079	22675
550				5431	8885		14403	27457	20445
575				4882	8590		13348	26798	16608
600				4102	8254		12077	26093	7917
625				2830	7895		10457	25332	
650					7503		7962	24499	
675					7067		3570	23572	
700					6552			22518	
725					5945			21280	
750					5143			19750	
775					4071			17687	
800					1945			14416	

